## **Technical Specification**

## Double cab pickup

Double cab pickup		Wall recipitor	1(One) Unit
S.N.	CRITERIA	REQUIREMENT	OFFERED SPECIFICATION
1	General	Double cab pickup, Right Hand Drive model	Make:
,1	General	with two and four wheel drive, suitable for driving both in ON-ROAD condition giving	Model:
		smooth economical performance and in OFF-	Country
	2 A	ROAD conditions capable of delivering strong adequate traction and maneuverability/stability	of Origin:
		needed for safe driving in rough, sandy or slippery and hilly road conditions in Nepal at an altitude	a <sup>0</sup>
		up-to 3000 meter and in ambient temperature	
		between -5°C to 50°C. Gross Vehicle Weight of	
		the vehicle shall not be less than 2700 Kgs.	
2	Engine	Water cooled diesel Engine, developing rated	Make:
2	Lingine	Power output not less than 45 kW and Torque not less than 190 N-m at rated RPM with an	Model:
		efficient fuel injection system having precisely	A
		control air fuel ratio for high efficiency in	
		response to all loads and operating conditions. The	£
		Engine shall be fully equipped with all necessary	
		items/ accessories and controlling devices for safe,	2
	A III	smooth, efficient and economical operation.	
3	Emission	The emission standard of the offered vehicle must	
	Standard	be in compliance with or superior than the	
		applicable Standard as prescribed by Nepal	
		Vehicle Mass Emission Standard which is to be	
		certified by Department of Transport	
		Management.	
4	Gauges	Fitted with all the gauges, indicators, signals as	
		necessary for efficient operation, functional	
	· ·	monitoring, vehicle performance and maintenance	
		that includes (but not limited to) Battery charge	8
		indicator, water temperature, fuel, oil pressure, transmission gauge etc. with all standard items of	
	9	offered model vehicle.	
5	Transmission	Manual shift, at least five forward and one	2
3	Tansinission	reverse, all forward synchromesh, floor mounted,	
		4WD engaged through control at driver.	

Page 1 of 3

		\$ 6 K 9 T 1 S S	
6	Ground	Higher ground clearance preferred	
	clearance	Committee Commit	
		Minimum 200 mm.	
7	Suspension	Suitable for toughest terrain, smooth ride, stable	
	1	handling and comfortable driving conditions. Coil	
	8	spring/Leaf springs/Torsion bar and shock	
		absorbers at front and rear.	
. 0	Tires	Standard Size	
8	75-500-500-500-500-500-500-500-500-500-5	Power assisted/Power Steering	8
9	Steering	Front Disc type, rear Disc/Drum type, hydraulic	
10	Brakes		
	h	operated on all wheels, and parking brake.	
11	Cab	4 doors, all metallic cab with insulated roof, right	
		hand drive, laminated glass windscreen, wipers,	
		glass windows on doors, through ventilation,	
		comfortable and adjustable seats for driver and	
		passenger, floor mats, two sun visors, and two side	
		view mirrors and rear view mirror. Rear body to	
		be metallic, pickup type with drop type tail board.	
10	Chassis and	Steel, heavy duty high rigidity frame structure	
12		suitable for rough road conditions with tow-hooks.	
- 10	Frame	Head light, tail and rear light, reversing light	
13	Accessories		
		and turn signals.	
		2. Cabin lights.	
		2. Cabin fights.	
		3. Speedometer / odometer.	
	4		
		4. Heavy duty front bumper.	
		5: Conservational with time and tube	9
		5. Spare wheel with tire and tube.	
		6. Mechanical/Hydraulic jack with handle.	
		7. Front seat belt for driver and co-passenger.	
		9. CD/MP3 Player, Preferably with Radio, MW	
			3
		& FM.	
.00		Equipped with all accessories offered in	
		standard model but not limited to the above	
		items.	
		Rems.	
14	Instructions	All signs and instructions in the vehicle shall be in	
11		English.	
-	-	Eugusu.	

Page 2 of 3

Mechanical Engineer

		7.0 May 200 Ma	
15	Manuals	One copy of the Operator's and Owner's Instructions and Maintenance manual in English shall be supplied with each vehicle.	n A
16	Tools	A set of tools, with a tool bag, as required for general maintenance shall be supplied with vehicle.	) 
17	Color	Standard Color	
18	Proven performance	1. The vehicle offered shall be a current model under standard production by the manufacturer for at least one year.	
		2. The bidder shall provide the manufacturer's data of the performance of the unit to include the fuel consumption, performance curve of the engine and production capacity.	
19	Warranty	Manufacturer shall provide a minimum of one year warranty after acceptance.	. *
20	Delivery	The Double-cab Pickup, RHD (4X4), 1 unit, shall be delivered to:	,
		लिसंखु पाखर गाउँपालिका, अत्तरपुर, सिन्धुपाल्चोक, नेपाल.	H ,

Note: The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specifications. Non-compliance of these major items will result in non-responsiveness of the bid offer.